

Your partner for everything outdoor



Extension Ladder Specifications



- Alflo rung joint for Twist-Proof performance
- Base section may be used as a single ladder
- Direct rung to rail connections
- Electrically non-conductive side rails
- Guides at top of base section and on bottom of fly section
- Interlocking side rails
- Mar-resistant molded end caps
- Pre-pierced holes for easy field installation of accessories
- Rail shield and shoe bracket protects rail
- Rope and pulley system
- Rope clamp ties rope to rung
- Rugged gravity spring locks
- Shoe with slip-resistant pad and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks



300lbs load capacity

Combined weight of user and materials
Type 1A Duty Rating

The D6200-2 fiberglass extension ladders have non-conductive rails making these ladders ideal for working near electricity.

With a duty rating of 300 pounds, the D6200-2 series is durable and long lasting. The exclusive ALFLO® rung joint means TWIST-PROOF® performance on the job. The TRACTION-TRED® D rungs are slip resistant and the side rails are interlocking.

The dual action feet are for use on hard or penetrable surfaces and swivel easily. The base and fly sections separate easily to use the base section as a single ladder. The durable rail shield bracket and shoe help protect the bottom of the rail.

The fly section rails are pre-pierced at the top for easy field installation of accessories.

Model #	Size	Reach Height	Max Working Length	Extended Length	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.
D6216-2	16 ft	15 ft	13 ft	13 ft	7	36.5
D6220-2	20 ft	19 ft	17 ft	17 ft	8.7	44.5
D6224-2	24 ft	23 ft	21 ft	21 ft	10.3	52
D6228-2	28 ft	27 ft	25 ft	25 ft	12	59.5
D6232-2	32 ft	31 ft	29 ft	29 ft	13.7	71.5
D6236-2	36 ft	34 ft	32 ft	32 ft	15.3	80.5
D6240-2	40 ft	37 ft	35 ft	35 ft	17	88.5



300lbs load capacity

Combined weight of user and materials
Type 1A Duty Rating

Outstanding **Ladders**

www.irvinforoutdoor.com



Irvin, Inc.
8105 Krauss Blvd
Suite 102
Tampa, FL 33619

Ph: 1-800-474-7846
Local: (813) 664-8945
Fax: (813) 621-6897
Email: info@irvinforoutdoor.com